



SERRE-CÂBLE à étrier « Estampé à chaud » Marquage CE

RÉF. 5274

ESTAMPÉ A CHAUD

Semelle et étrier ACIER

position correcte des serre-câbles
étriers sur brin mort, semelles sur brin tirant



CODE	A	B	C	D	E	F	G	H	I	K	L	M	N	P	Q	R	S	T	V
câble Ø mm	3-4	5	6	8	10	11	12	14	16	18	20	22	24	28	30	32	38	45	50
A en mm	21	25	30	33	38	40	45	46	53	59	60	64	70	80	80	92	95	115	115
D en mm	M4	M5	M6	M6	M8	M8	M10	M10	M10	M12	M12	M12	M12	M14	M14	M16	M16	M16	M16
L en mm	20	24	34	34	44	45	55	55	63	78	78	81	86	110	112	115	130	158	158
Poids en kg	0,01	0,02	0,03	0,04	0,07	0,08	0,12	0,14	0,18	0,26	0,29	0,30	0,38	0,56	0,71	0,91	1,03	1,45	1,45




SERRE-CÂBLE à étrier – INOX


RÉF. 5285

Acier INOX
AISI 316

position correcte des serre-câbles
étriers sur brin mort, semelles sur brin tirant



CODE	A	B	BA	C	D	E	F	G	H	I	J	K	L	M	N
câble Ø mm	2	3-4	5	6	8	10	12	14	16	18	20	22	25	28	32
C (mm)	10	8	9	11	12	14	16	18	20	21	22	23	24	30	37
D (mm)	3	4	5	6	6	8	10	10	10	12	12	12	12	14	16
H (mm)	18	22	24	33	35	43	54	54	65	80	80	85	85	105	110
L (mm)	18	22	24	30	33	37	45	46	53	55	58	64	69	80	92
largeur semelle (mm)	10	14	16	18	20	22	25	27	30	31,5	33	34	39	42	46
Poids (kg)	0,01	0,01	0,02	0,03	0,04	0,07	0,12	0,15	0,2	0,24	0,27	0,31	0,36	0,60	0,90



INOX AISI 316

